



單位:mm

SCREW SIZE		BALL DIA.	EFFECTIVE TURNS	BASIC RATE LOAD/(kgf)		BALLNUT DIMENSION										
O.D.	LEAD			Dynamic (1×10 ⁴ REV) Cam	Static Coam	O.D.	Length	Flange					Oil Hole	Assembly Hole	STIFFNESS	Nut Model NO.
						D	L	A	T	W	G	H	Q	X	kgf/μm	
15	5	3	4	1210	2130	28	39	48	10	38	20	40	M6×1P	5.5	22	FSDN1605V-4.0P
	10		3	950	1650	28	47	48	10	38	20	40	M6×1P	5.5	17	FSDN1605V-3.0P
	16		3	910	1600	28	64	48	10	38	20	40	M6×1P	5.5	17	FSDN1605V-3.0P
20	5	3.175	4	1570	3270	36	40	58	10	47	22	44	M6×1P	6.6	28	FSDN2005B-4.0P
	20		4	1460	3120	36	58	58	10	47	22	44	M6×1P	6.6	28	FSDN2020B-4.0P
25	5	3.175	5	2130	5230	40	46	62	10	51	24	48	M6×1P	6.6	41	FSDN2505B-5.0P
	10		4	1740	4120	40	60	62	10	51	24	48	M6×1P	6.6	33	FSDN2510B-4.0P
	25		4	1610	3900	40	68	62	10	51	24	48	M6×1P	6.6	33	FSDN2525B-4.0P
32	5	3.175	6	2800	8190	50	53	80	12	65	31	62	M6×1P	9	59	FSDN3205B-6.0P
	10		5	3240	8480	50	73	80	12	65	31	62	M6×1P	9	52	FSDN3210C-5.0P
	20	3.969	4	2600	6640	50	101	80	12	65	31	62	M6×1P	9	42	FSDN3220C-4.0P
	32		4	2460	6340	50	84	80	12	65	31	62	M6×1P	9	41	FSDN3232C-4.0P
38	10	6.35	5	6500	15610	63	78	93	15	78	35	70	M8×1P	9	64	FSDN3810F-5.0P
	20		4	5250	12240	63	107	93	15	78	35	70	M8×1P	9	52	FSDN3820F-4.0P
	40		4	4940	11770	63	104	93	15	78	35	70	M8×1P	9	51	FSDN3840F-4.0P

Note:

1. Cam and Coam represent the enhanced dynamic- and static load. Their calculations referred to the standard of DIN 69051.

2. Stiffness of nut:

Stiffness values listed above are derived from theoretical formula to the elastic deformation between thread grooves and balls while axial load is 30% dynamic load rating.