



1	2	3	4	5	6	7	8	
2								
3								
4								
5								
6								
7								
8								




Specification after combined	XYGT321-P1-600-250-50-M-K-F206
------------------------------	--------------------------------








	Model	GT1H8-L5-600-BG-M20-C4
	Designated motor model	Mitsubishi 200W : HG-KR23(Customer supply)
	Motor shaft keyway	None
	Sensor	3 units of EE-SX674 externally with 2m cable
	Max. motor speed	3000rpm/min
X	Max. linear speed	250mm/sec
	Acceleration and deceleration	200ms(0.2sec)
	Repeatability	±0.01mm
	Customization item	None
	Model	GT1H5-L5-250-BR-M10B-C4
	Designated motor model	Mitsubishi 100W+brake : HG-KR13B(Customer supply)
	Motor shaft keyway	None
	Sensor	3 units of EE-SX674 externally with 2m cable
	Max. motor speed	3000rpm/min
	Max. linear speed	250mm/sec
Z	Acceleration and deceleration	200ms(0.2sec)
	Repeatability	±0.01mm
	Customization item	None
	Model	GT1H4-L2.5-50-BG-M05-C4
	Designated motor model	Mitsubishi 50W : HG-KR03(Customer supply)
	Motor keyway	None
	Sensor	3 units of EE-SX674 externally with 2m cable
	Max. motor speed	3000rpm/min
	Max. linear speed	125mm/sec
	Acceleration and deceleration	200ms(0.2sec)
	Repeatability	±0.01mm
	Customization item	None
	Y Axis Horizontal payload	2 kg
	Customization item	None



X,Z cable chain : 1500.50.038.0



C view

[illegible]