Specification after combined		XYGT221-G1-500-500-300-K-F300
X1	Model	GTH5-L10-500-BC-F300
	Designated motor model	None
	Motor shaft keyway	None
	Sensor	None
	Customization item	1.Ball screw and mounting bracket non-standard (滾珠螺桿及馬達固定座特注) 2.Additional bearing(追加軸承) 3.Additional hand wheel，Fixed hole diameter □6 (Customer supply) (追加手輪，固定孔直徑6)(客戶提供)
X2	Model	Type 15-L680-10/10N-single linear block
Y	Model	GTH4-L2.5-500-BC-F300
	Designated motor model	None
	Motor shaft keyway	None
	Sensor	None
	Customization item	1.Ball screw and mounting bracket non-standard (滾珠螺桿及馬達固定座特注) 2.Additional bearing(追加軸承) 3.Additional hand wheel，Fixed hole diameter □6 (Customer supply) (追加手輪，固定孔直徑6)(客戶提供)
Z	Model	GTH5-L10-300-BC-F300
	Designated motor model	None
	Motor shaft keyway	None
	Sensor	None
	Customization item	1.Ball screw and mounting bracket non-standard (滾珠螺桿及馬達固定座特注) 2.Additional bearing(追加軸承) 3.Additional hand wheel，Fixed hole diameter □6 (Customer supply) (追加手輪，固定孔直徑6)(客戶提供)
Z2	Model	Type 15-L460-10/30N-single linear block
Z Axis vertical payload		2 kg
Customization item		1. 使用60X60鋁擠型 2. 滑台作動有晃動風險，故不保固











Product	Multi Axis Table	Specification	XYGT221-G1-500-500-300-K-F300	Item		Scale		Part number		Surface treatment		Heat treatment	

△	Modification	Date	Modified by	Surface Roughness	G 0.8S 4 / 3.2S 3 / 25S 2 / 100S 1 / ~ 0
1				General tolerance is not marked	1.Scale tolerance by vernier caliper ±0.5 when below 300 2.Pitch tolerance ±0.15 3.Square tolerance ±0.015
2				Scale tolerance	±0.5 when below 300 ±0.7 when between 300~600 ±1.0 when between 600~1000 Unmarked chamfer : C0.5 Unmarked corner rounding : R0.5

Unit : mm	Audit	Design	Draw	TOYO
	Ellen 2017.10.06		Ellen 2017.10.06	
Path :				Page